

# STUD & TRACK

## Drywall Partitioning

A range of vertical metal studs combined with ceiling and floor tracks; together they form a framework which is designed to accept gypsum wallboards in single or double thickness. Libra stud and track is available in several widths, each of which has been tested to a variety of fire, acoustic and structural standards. Studs have a knurled face to assist straight screw penetration when fixing wallboards with drywall screws; this allows the contractor to complete drywalls with the minimum amount of effort.

### ► C STUD Drywall Metal 'C' Stud Partitioning

#### C STUD

Detail	Ref	Description	Average Pack/Carton Details			Pallet Details H x W x L (mm)
			Pcs	Standard Length mm	Kg	
	FS48	C Stud 34 x 48 x 32	100	2400	133	275 x 350 x 2400
				2700	150	275 x 350 x 2700
				3000	166	275 x 350 x 3000
				3600	200	275 x 350 x 3600
	FS50	C Stud 34 x 50 x 32	100	2400	135	285 x 350 x 2400
				2700	152	285 x 350 x 2700
				3000	168	285 x 350 x 3000
				3600	202	285 x 350 x 3600
	FS60	C Stud 34 x 60 x 32	100	2400	152	340 x 360 x 2400
				2700	171	340 x 360 x 2700
				3000	190	340 x 360 x 3000
				3600	227	340 x 360 x 3600
	FS70	C Stud 34 x 70 x 32	100	2400	156	385 x 350 x 2400
				2700	175	385 x 350 x 2700
				3000	195	385 x 350 x 3000
				3600	233	385 x 350 x 3600
	FS73	C Stud 34 x 73 x 32	100	2400	160	410 x 350 x 2400
				2700	180	410 x 350 x 2700
				3000	200	410 x 350 x 3000
				3600	240	410 x 350 x 3600
	FS92	C Stud 34 x 92 x 32	100	3000	211	495 x 350 x 3000
				3600	253	495 x 350 x 3600
				4200	295	495 x 350 x 4200
			FS146	C Stud 34 x 146 x 32	100	3000
	3600	353			306 x 875 x 3600	
	4200	412			306 x 875 x 4200	

#### PLEASE NOTE!

All 'C' Studs are boxable and both legs are 'knurled' for ease of drywall screw penetration.

Components are manufactured from Hot Dip Galv. to EN10142.

A range of fire, acoustic and structural certificates are available on request.

Other sizes, lengths and thickness's are available on request.